



Polymers

Table of contents

■ Casting resin model and mould construction	2
■ Modelling and tooling boards	2
■ Model pastes	2
■ Silicone molding systems	2
■ Silicone gels for electrical and electronics applications and damping elements	2
■ Gelcoats / Coupling layers	3
■ Laminating resins	3
■ Casting resin for producing rubber-like and thermoplast-like parts	3
■ Casting systems	3
■ Wax sheets	3
■ Mould release agents / Mould sealers	3
■ Resins for the manufacture of fibre reinforced plastics (structural composites)	3
■ Silicone elastomers for the electrical industry	4
■ Epoxy casting resin for the electrical and electronics industries	4
■ Polyurethane casting resin for the electrical and electronics industries	4
■ Waterproofed casting resin for electrical applications	4
■ Accelerators	5
■ Colour pastes	5
■ Filling materials	5
■ Gelcoats	5
■ Polyester resins	5





Casting resin model and mould construction

Conventional processes in model and mould-making are being continuously completed through innovative technologies such as rapid prototyping and rapid tooling. With these processes the emphasis is mainly on the cost-advantages for small and medium-sized batch production, as well as rapid availability of tooling in comparison to conventional tool making. We offer a comprehensive range in the fields of casting-resins, model-making pastes and tooling boards for making models and moulds. For many years, Bodo Möller Chemie has been on hand as a knowledgeable partner for a very wide variety of industries; and we offer tried and tested system solutions to customers' specific requirements.

Modelling and tooling boards

RenShape® tooling materials are easy to work, seal-tight, as well as impact- and temperature resistant. Tooling boards are excellently suited to the manufacture of large and complex models and can be reproduced in a few hours by means of stereolithography or CNC machines. RenShape® prototype models can be painted to match the production component. For the repair or glueing of plates we supply you with the appropriate repair-kit.

- RenShape® Modelling and tooling boards
- Araldite® 2-component epoxy adhesives
- Ureol® 2-component PU adhesives

On request larger mould-parts/half-moulds can be cast in a block to customer specifications. For further information consult our Net-Size Casting™ service, provided in collaboration with the Huntsman Group.

Silicone molding systems

In order to multiply objects - like sculptures, models, surface textures -, first a casting of the so-called master pattern is needed. For the production of this form, flexible materials, "casting masses" are best suitable. Our comprehensive range of RTV-2 silicone elastomers is exactly co-ordinated with the requirements in practice. Our products permit casting all degrees of difficulty for each reproduction material. By these elastomers the development of new casting techniques as well as casting of very aggressive form resins became possible. Rhodorsil® / Bluesil™ RTV-2 silicone elastomers have some specific characteristics, which offer our customers numerous advantages.

- Rhodorsil® / Bluesil™ RTV-2 Silicones for molding



Silicone gels for electrical and electronics applications and damping elements

Silicone gel is a two component silicone elastomer that crosslinks at room temperature by polyaddition reaction. The polymerisation can be accelerated by heating. After the mixing of the components, the handling of the silicone gel occurs through moulding. Main application areas of silicone gels are the electric and electronic industry for the protection of filigree devices such as hybrids, semi-conductors, conductor boards etc. Silicone gels are very stable both at low and high temperatures and are used in temperature ranges between -50°C and approx +200°C. Furthermore, silicone gels are used in high-voltage applications where their main advantages are the low dielectric constant and with low loss factors. In the physiological area silicone gels are also used for padding applications like bicycle saddles, shoes or keyboard wrist pillows. Silicone gels are also used and ideal for the absorption of sound waves and for the damping of vibrations and oscillations.

- Rhodorsil® / Bluesil™ RT Gel 2-component silicone gel





Gelcoats / Coupling layers

Our surface resins are manufactured on a basis of epoxy resins and polyurethane. They are easy to file and polish, as well as elastic and heat-resistant.

RenGel™ Gel coatings / linking layers

Laminating resins

Laminating and all-purposes resins based on epoxy resin are available under the trade name RenLam™. They are used in the production of workable cover-layers for prototypes. For infusion processes (RTM and RIFT) we offer special infusion resins, which make it possible to create even large components in a single infusion process.

RenLam™ Epoxy-resin-based laminating systems

Casting resin for producing rubber-like and thermoplast-like parts

RenPim™ are quick-hardening dual-component polyurethane systems which are particularly suitable for prototypes and one-offs, since they are very similar in appearance and physical properties to the technical thermoplastics used in series production of the parts.

RenPim™ 2-component PU systems for mechanical, manual and vacuum moulding



Casting systems

With the aid of our moulding and quick-moulding resins, prototypes and mould-components can be quickly produced. For moulding these, you can choose from a building-block system of available moulding-resins with a very wide range of E-moduli.

RenCast™ 2-component epoxy moulding-resin systems

RenCast™ 2-component polyurethane quick-moulding resins

Wax sheets

For the forming of spacing layers, we offer self-adhering wax foils in various strengths.

Freeman wax sheet® Thermostable wax foils

Mould release agents / Mould sealers

Separators have always been indispensable aids.

We supply wax-based, silicon-free mould release agents for cold- and hot hardening systems as well as mould-sealers for sealing plastics, rubber, wax etc.

Resins for the manufacture of fibre reinforced plastics (structural composites)

Plastics have their established place in industrial manufacturing, and here it is chiefly fibre-reinforced plastics that are of great importance in the manufacture of high stress-bearing components. Fibre-composite materials bring together properties and design possibilities, which are not always to be found in conventional materials. We supply high-tech resin systems, which are already an established element in the aircraft and space industries, in the medical and electronics industries and even in the manufacture of sports equipment.

In recent years the demand for fibre-composite systems has risen steeply. Araldite epoxy and phenol resin systems are notably superior to other types of resin with regard to the properties that are important for high-quality components (tension-resistance, rigidity, and resistance to shrinkage, fracture-expansion, and temperature).

Bodo Möller Chemie offers resin systems for the production of prepregs, for resin transfer moulding and resin infusion processes, as well as for hand lamination, filament winding and pultrusion. The molecular structure of epoxy resin systems is

a linear chain with reactive epoxy groups at the ends, which are responsible for a bond with the hardener. We supply hot- as well as cold-hardening systems. Epoxy resins can react with many different hardeners, thus pre-formulated products can be supplied, or else so-called "building-blocks", which permit a multiplicity of resin/hardener combinations and allow great freedom in formulating the system.

Araldite®	Epoxy resins
Araldite®	Phenol resins
Aradur®	Curing systems usually amino based
Araldite®/Aradur®	Formulated resin-hardener systems
Rhodefal®	Polyamidoimide (protective lacquer)
Matrimid®	Polyimide
Kerimid®	Bismaleimide resins
Qatrex®	Single-component epoxy resin systems
Tactix®	Epoxy resins



Silicone elastomers for the electrical industry

We offer with Rhodorsil® / Bluesil™ a complete range of silicone elastomers for the electrical industry. A fifty years experience in producing and developing technical Silicones makes Rhodorsil® / Bluesil™ to a powerful and innovative trademark in the industry. There is no limit of the use of liquid silicone elastomers in the Electrical and Electronic industries, especially when protection of components against harmful environmental effects is required. Polyaddition curing systems are the preferred insulating materials for these applications. Their acceptance is due to several factors including their excellent dielectric properties, mechanical strength, shock resistance, moisture resistance, excellent adhesion properties, aging and chemical resistance. Rhodorsil® / Bluesil™ RTV-2 silicone elastomers are room temperature curing systems for all types of potting, casting, impregnating or dipping. Rhodorsil® / Bluesil™ RT Gels are 2-component silicone oils curing by polyaddition reaction. A low level of viscosity allows a very easy mixing of the components. After two components mixing, the very fluid liquid is transformed after curing into a self elastic, translucent gel which is preferable used in insulating and electrical parts protection.

Rhodorsil® / Bluesil™ pastes are made of polydimethyl siloxanic oil thickened with inert fillers. Rhodorsil® / Bluesil™ pastes are mainly used as sealants and electrical insulants.

Rhodorsil® / Bluesil™ RTV 2 2-component silicone elastomer
Rhodorsil® / Bluesil™ Pastes Silicone pastes



Epoxy casting resin for the electrical and electronics industries

Insulation is a crucial factor for the good functioning and operational life of many electronic components such as generators, electric motors, transformers, condensers and electrical appliances. It must be capable of securely preventing disruptive electrical discharges, diffusing any heat radiation and sustaining mechanical forces without problem.

Araldite® Epoxy coating systems, resin/hardener combinations and individual components
Araldite® Epoxy impregnation resin systems
Aratherm™ Highly heat-conductive epoxy moulding compounds

Polyurethane casting resin for the electrical and electronics industries

Arathane™ systems are polyurethane casting systems curing at room temperature. They meet the highest specifications regarding physical and chemical demands. These systems are highly cost effective and are used for transformers or for electronic devices. We offer a very extensive range of polyurethane casting systems like self-extinguishing according to UL 94 V0 and NF F 16-102 or heat resistant until +155°C (heat class F according to IEC 60085). Also suitable for explosive applications according to IEC 50028, highly heat-conductive, transparent, UV stable etc.

Arathane™ Polyurethane casting system



Waterproofed casting resin for electrical applications

Specially developed cycloaliphatic Araldite® epoxy casting systems are highly suitable as coating systems. They have recently been equipped with hydrophobic properties for low-voltage electronic applications, and also for use in the moulding of high-tension components, in order to obtain long operational life and resistance to environmental influences.

Araldite® Cycloaliphatic epoxy casting systems



Accelerators

The choice of a suitable type of accelerator and its optimal concentration can make it possible to accelerate the speed of reaction by many times. Additives with a catalytic effect are mainly from the group of tertiary amines.

Accelerator DY™ Amine accelerator



Polyester resins

Our high-quality resin systems (unsaturated polyester resins, epoxy vinyl ester resins) can be used in many applications. Bodo Möller Chemie offers a wide range of polyester resins for composites applications. Our polyester resins are resistant against low acids and bases as well as against fuel and oil. Polyester resins form long and unbranched polymers but which can also be cross-linked. Crystic® resin systems comprise also fire retardant systems which are halogen and antimony free. To achieve this, so-called functional groups are added to the molecule. They cross-link and cure. Unsaturated polyester resins contain double bonds curing with styrol or other reactive diluents with the aid of peroxides like for example dicumyle peroxide, dibenzoyl peroxide or methyl ethyl ketone peroxide. We offer you a comprehensive product portfolio for a wide variety of applications like SMC, RTM, CMR, Vacflo, etc. Tell us your composites application and we will offer you the best suiting resin system.

Crystic® 2.406PA	Orthophthalic resins
Crystic® 199	Isophthalic and isophthalic/ NPG's resins
Crystic® VE671	Vinyl Ester resins
Crystic® 344A	Fire retardants resins
Crestapol® 1210	Tough, low viscosity closed mould resin exhibiting very rapid cure

Colour pastes

High-viscosity, solvent-free specialized dye-pastes are used to colour epoxy and polyurethane mouldings and moulded parts of all kinds.

Araldite® DW Colouring pastes

Filling materials

Filling materials with special functions are very widely used in the electronics industry. Fillers can have an influence on a number of important properties. For epoxy systems we supply aluminium oxide, aluminium hydroxide, dolomite, mica, chalk, talc, ground quartz and wollastonite.

Gelcoats

A gelcoat is a material used to provide a high-quality finish on the visible surface of a fibre-reinforced composite material. The gelcoat protects the subjacent lacquer against moisture and pressure damages by sealing the composite. In addition the gelcoat gives the manufactured component a glossy surface which improves the aesthetic appearance of the article. When gelcoats are used indoors, it's relatively easy to preserve a lasting and attractive surface. But with outdoor applications, if the gelcoat is not specifically designed for the application, problems can occur like changing colour, fading, loss of gloss or abrasion. This can be the case particularly in the marine industry. The Scott Bader gelcoats we offer are very high-quality gelcoats and famous for over 60 years around the world for quality and reliability. The Crystic® Gelcoats have excellent weathering performance to suit demanding external applications in marine, building, transport and industrial markets where exterior durability is critical. They are widely used in wind power, pipeline construction and rehabilitation. Crystic® Gelcoats are easy to handle and enable to get tough and long-lasting surfaces. The finish has a low porosity which makes the gelcoat easy to repair. Furthermore Crystic® Gelcoats are very flexible and resist to the demoulding process without crack formation even by complicated components. The initial gloss is very high which makes polishing less time-consuming. All gelcoats have to pass severe tests, 12 months duration time, before they can be included in the product portfolio. We offer a wide range of brush and spray gelcoats, including isophthalic/ NPG, fire retardant, sandable or tooling gelcoats, topcoats, barriercoats and epoxy bonding gelcoats.

Crystic® LS 88PA	Isophthalic brush gelcoat with excellent water resistance
Crystic® LS 96PA	ISO spray gelcoat with good handling properties
Crystic® 30PA	Ultimate superior weathering gelcoat (Iso/NPG) with excellent water resistance
Crystic® 48PA	Fire retardant gelcoat
Crystic® 42PA	Sandable gelcoat for easy and precise abrasion
Crystic® 14PA	Superior tooling gelcoat with excellent heat and chemical resistance and superior gloss
Crystic® X 103KH	Topcoat with low viscosity which cures tack-free
Crystic® GC 251PA	Gelcoat for use with epoxy laminating and infusion systems
Crestacoat 5000PA	Barriercoat for improving surface aesthetics





Austria

Bodo Möller Chemie Austria GmbH
Am Hafen 6
A-2100 Korneuburg
Phone: +43 (0)2262 62257
info@bm-chemie.at
www.bm-chemie.at

Benelux

Bodo Möller Chemie Benelux N.V.
Vosseschijnstraat 40, Haven 140
B-2030 Antwerpen
Phone: +32 (0)3 235 21 35
info@bm-chemie.be
www.bm-chemie.be

Denmark

Bodo Möller Kemi Danmark Aps
Dam Holme 14-16
DK-3660 Stenlose
Phone: +45 4816 3470
info@bm-kemi.dk
www.bm-kemi.dk

Finland

Bodo Möller Chemie Nordic Oy
Kauppakartanonkatu 7A
FI-00930 Helsinki
Phone: +358(9)- 682 9010
info@bm-chemie.fi
www.bm-chemie.fi

France

Bodo Möller Chimie France SAS
22 Rue Pierre Martin
F-72100 Le Mans
Phone: +33 (0)243 240 429
info@bm-chemie.fr
www.bm-chemie.fr

Italy

Bodo Möller Chimica Italia S.r.l
Largo Umberto Boccioni, 1
IT-21040 Origgio (VA)
Phone: +39 02-96280575
info@bm-chimica.it
www.bm-chimica.it

Poland

Bodo Möller Chemie Polska Sp. z o.o.
Ul. Naramowicka 150
PL-61-619 Poznań
Phone: +48 (0)61 822 09 75
info@bm-chemie.pl
www.bm-chemie.pl

Sweden

Bodo Möller Chemie Sweden AB
Önnereds Brygga 7
SE-421 57 Västra Frölunda
Phone: +46 (31) 69 89 51
info@bm-chemie.se
www.bm-chemie.se

Switzerland

Bodo Möller Chemie Schweiz AG
General Guisan-Str. 11
CH-8400 Winterthur
Phone: +41 (0) 52 203 19 30
info@bm-chemie.ch
www.bm-chemie.ch

South Africa

Bodo Möller Chemie South Africa
P O Box 210815, The Fig Tree
ZA-6033 Port Elizabeth

Germany
Bodo Möller Chemie GmbH
Senefelderstrasse 176
D-63069 Offenbach / Main
Phone.: +49 (0)69 838326-0
Fax: +49 (0)69 838326-199
info@bm-chemie.de
www.bm-chemie.de